



1L | 1113301-001

4L | 1113301-004

5L | 1113301-005

10L | 1113301-010

20L | 1113301-020

20L | 1113301-B20

60L | 1113301-060

208L | 1113301-208

1000L | 1113301-700

RAVENOL 4-Takt Gardenoil

Kategorie: Other engine oil

Artikelnummer: 1113301

Viscosity: 30

Specification: API CD, API SF

Oil type: Mineral

Recommendation: CCMC G4, Honda, Husqvarna, MB 227.0, MIL-L-2104 D, MIL-L-46152 B, Oleo-Mac, Stihl

Application: Hobby and garden

RAVENOL 4-Takt Gardenoil HD 30 is a mineral mono grade engine oil formulated for use in 4-stroke lawn mowers. Special additives ensure an excellent protection against wear and corrosion. Usable at normal operating temperatures. Constant viscosity, no shearing losses.

RAVENOL 4-Takt Gardenoil HD 30 usable especially where the normal operating temperatures will be expected. The oil viscosity remains constantly at the operation temperature over the whole service interval.

Application Note

RAVENOL 4-Takt Gardenoil HD 30 is suitable for use in 4-stroke lawn mowers under normal operating temperatures.

Characteristics

- Protection against corrosion
- Good shear stability
- High oxidation stability
- Excellent viscosity-temperature behavior
- Enhanced levels of detergent and dispersant for cleaner engines
- Very good cold starting properties
- Prevents formation of deposits and black sludge

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	876,0	EN ISO 12185
Colour		braun	VISUELL
Viscosity at 100 °C	mm²/s	12,1	DIN 51562-1
Viscosity at 40 °C	mm²/s	103,3	DIN 51562-1
Viscosity Index VI		106	DIN ISO 2909
Pourpoint	°C	-24	DIN ISO 3016
Flashpoint	°C	248	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.