



RAVENOL Regular 30

Kategorie: Oltimer engine oil (Classic products)

Artikelnummer: 1113302

Viscosity: 30

Specification: API SA

Oil type: Mineral

Application: Passenger car, Hobby and garden



20L | 1113302-020

20L | 1113302-B20

60L | 1113302-060

RAVENOL Motorenoel SAE 30 W Regular is a non-alloyed engine oil, it is manufactured using carefully selected pure mineral raffinates. It provides oxidation stability, it is non-foaming and also has excellent viscosity-temperature characteristics. Thanks to its low setting point, this oil can be used in both low and high temperatures and guarantees perfect lubrication.

Application Note

RAVENOL Motorenoel SAE 30 W Regular SA is used in passenger car petrol and diesel engines where the API specification SA is required.

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		braun	VISUELL
Viscosity at 100 °C	mm ² /s	11,0	DIN 51562-1
Viscosity at 40 °C	mm ² /s	92,0	DIN 51562-1
Viscosity Index VI		105	DIN ISO 2909
Density at 20 °C	kg/m ³	882,0	EN ISO 12185
Flashpoint	°C	245	DIN EN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.