



RAVENOL SVE Standard Viscosity Ester Oil SAE 5W-30



1L | 1116101-001

5L | 1116101-005

10L | 1116101-010

20L | 1116101-020

20L | 1116101-B20

60L | 1116101-060

208L | 1116101-208

Kategorie: Passenger car motor oil

Artikelnummer: 1116101

Viscosity: 5W-30

Specification: ACEA A3/B4, API CF, API SN

Oil type: Semi-synthetic

Recommendation: BMW Longlife-01, MB 229.5, VW 501 01, VW 502 00, VW 505 00

Application: Passenger car

The semi synthetic motor oil **RAVENOL SVE Standard Viscosity Ester Oil SAE 5W-30** is a new development with a unique formula specifically for high mileage vehicles of approx. 100,000 km and more. **RAVENOL SVE Standard Viscosity Ester Oil SAE 5W-30** is particularly recommended for vehicles with high mileage, petrol and diesel engines, with and without turbocharge and direct injection.

The extremely conditioning and cleaning additives in **RAVENOL SVE Standard Viscosity Ester Oil SAE 5W-30** revitalise critical engine parts and particularly protect gaskets. This can extend the life, particularly in older vehicles with high mileage.

RAVENOL SVE Standard Viscosity Ester Oil SAE 5W-30 features outstanding lubrication and excellent shear stability, and the added conditioners simultaneously reduce oil consumption and protect from sludge and wear.

Application Note

RAVENOL SVE Standard Viscosity Ester Oil SAE 5W-30 is perfectly suited for year-round use in high mileage petrol and diesel engines with 100,000 km and more, and promotes low oil consumption. A very clean engine is guaranteed.

RAVENOL SVE Standard Viscosity Ester Oil SAE 5W-30 extends the life of the engine in older vehicles by reducing oil consumption and protecting from sludge and wear. A very clean engine is guaranteed.

Characteristics

- High wear protection
- Fuel saving because of easy running characteristics
- Outstanding detergent and dispersant properties prevent sludge
- High oxidation stability for a long life
- Brilliant cold cranking behaviour through special additives
- Excellent viscosity-temperature behaviour
- Low vaporisation characteristics, therefore reduced oil consumption
- Suitable for catalytic converters

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	850,0	EN ISO 12185
Colour		braun	VISUELL
Viscosity at 100 °C	mm²/s	12,35	DIN 51562-1
Viscosity at 40 °C	mm²/s	72,33	DIN 51562-1
Viscosity Index VI		170	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	3,57	ASTM D5481
CCS Viscosity at -30 °C	mPa*s	5590	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	24.100	ASTM D4684
Pourpoint	°C	-36	DIN ISO 3016
Noack Volatility	% M/M	9,3	ASTM D5800
Flashpoint	°C	236	DIN EN ISO 2592
tbn	mg KOH/g	9,8	ASTM D2896
Sulphated Ash	%wt.	1,31	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.