




20L | 1123710-020
20L | 1123710-B20
60L | 1123710-060
208L | 1123710-208
1000L | 1123710-700

RAVENOL Super Truck SAE 10W

Kategorie: Truck engine oil

Artikelnummer: 1123710

Viscosity: 10W

Specification: ACEA B4, ACEA E2, API CF-4

Oil type: Mineral

Recommendation: MAN 270, MB 228.0, MTU Typ 1, Voith DIWA

Application: Truck

RAVENOL Super Truck SAE 10W is high alloyed HD engine oil with synthetic additives. It is suitable for diesel engines of trucks even with turbo charging. The high additive content guarantees an excellent effect regarding detergent, dispersant and anticorrosion characteristics.

RAVENOL Super Truck SAE 10W is a top-quality product with high safety reserves.

Application Note

RAVENOL Super Truck SAE 10W is mono grade motor oil for use in truck diesel engines with or without turbo charger.

Characteristics

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts
- Reduced emissions

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	864,0	EN ISO 12185
Colour		braun	VISUELL
Viscosity at 100 °C	mm²/s	6,9	DIN 51562-1
Viscosity at 40 °C	mm²/s	42,4	DIN 51562-1
Viscosity Index VI		122	DIN ISO 2909
Pourpoint	°C	-39	DIN ISO 3016
Flashpoint	°C	234	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.