



1L | 1133100-001

4L | 1133100-004

5L | 1133100-005

10L | 1133100-010

20L | 1133100-020

20L | 1133100-B20

60L | 1133100-060

208L | 1133100-208

1000L | 1133100-700

RAVENOL MGS SAE 15W-40

Kategorie: Other engine oil

Artikelnummer: 1133100

Viscosity: 15W-40

Specification: ACEA A3/B4, ACEA E2, API CF-4, API SJ

Oil type: Mineral

Approvals: TEDOM Group 1P (61-0-0281.2)

Recommendation: MB 226.9

Application: Industry

RAVENOL MGS SAE 15W-40 is high performance multi-grade engine oil suitable for the lubrication of natural gas engines. It has excellent lubricating film adhesion, very good shear stability and an excellent cleaning power and high resistance to aging.

Application Note

RAVENOL MGS SAE 15W-40 is suitable to apply as a multi-grade engine oil for natural gas engines.

Characteristics

- A very good shear stability
- Very good cold start behaviour
- A high oxidation stability
- Avoids the formation of accumulations of mud (black sludge)
- An excellent viscosity temperature behaviour
- No problems with the use in catalyst vehicles
- Convincing detergent and dispersant attributes
- High security reserves even under limited lubrication conditions

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	873,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm²/s	14,4	DIN 51562-1
Viscosity at 40 °C	mm²/s	107,2	DIN 51562-1
Viscosity Index VI		137	DIN ISO 2909
Pourpoint	°C	-30	DIN ISO 3016
Flashpoint	°C	242	DIN EN ISO 2592
tbn	mg KOH/g	8,1	ASTM D2896
Sulphated Ash	%wt.	1,1	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.