

RAVENOL Schneefräse 4-Takt SAE 5W-30



1L | 1151105-001

4L | 1151105-004

Kategorie: 4 stroke engine oil

Artikelnummer: 1151105

Viscosity: 5W-30

Specification: ACEA A5/B5, API SL, API SM

Oil type: Full synthetic

Recommendation: Ariens, Briggs&Stratton, Caiman, Canadiana, Craftsman, CubCadet, Honda, Husqvarna, McCulloch, MTD, Murray, Partner, Snapper, Stiga, Swisher, TORO, White Outdoor, Yard-Man

Application: Hobby and garden

RAVENOL Schneefräse 4-Takt SAE 5W-30 is high quality full synthetic green coloured four-stroke engine oil.

RAVENOL Schneefräse 4-Takt SAE 5W-30 is specially designed for 4-stroke snow blowers. Excellent wear protection also by high pressure, excellent corrosion protection. Because of the noticeable fuel economy **RAVENOL Schneefräse 4-Takt SAE 5W-30** contributes to the reduction of pollutant emissions and protecting the environment.

Application Note

RAVENOL Schneefräse 4-Takt SAE 5W-30 is fuel efficient engine oil special conceived for 4-stroke snow blower engines.

Characteristics

- Fast oiling of the engine, also by low temperatures
- Low oil consumption because of the low evaporation tendency
- Excellent wear protection by high pressure
- Excellent corrosion protection
- Safety towards sludge, coking, leaking and corrosion also in unfavourable operational conditions
- No oil caused deposits in combustion chambers, in piston ring zone and on valves
- Neutrality against seal materials

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	849,0	EN ISO 12185
Colour		grün	VISUELL
Viscosity at 100 °C	mm²/s	10,0	DIN 51562-1
Viscosity at 40 °C	mm²/s	56,6	DIN 51562-1
Viscosity Index VI		165	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	3,08	ASTM D5481
CCS Viscosity at -30 °C	mPa*s	4300	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	14.000	ASTM D4684
Pourpoint	°C	-39	DIN ISO 3016
Noack Volatility	% M/M	9,4	ASTM D5800
Flashpoint	°C	240	DIN EN ISO 2592
tbn	mg KOH/g	10,9	ASTM D2896
Sulphated Ash	%wt.	1,1	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.