



1L | 1151211-001

4L | 1151211-004

10L | 1151211-010

20L | 1151211-020

20L | 1151211-B20

60L | 1151211-060

208L | 1151211-208

1000L | 1151211-700

RAVENOL WATERCRAFT 4-Takt

Kategorie: 4 stroke engine oil

Artikelnummer: 1151211

Specification: API SL, NMMA FC-W

Oil type: Synthetic

Application: Marine

RAVENOL WATERCRAFT 4-Takt belongs to viscosity grade SAE 15-W40.

RAVENOL WATERCRAFT 4-Takt is a synthetic 4-stroke engine oil based on high quality base oils together with a selected additive package designed especially for use in marine petrol engines.

The formulation of **RAVENOL WATERCRAFT 4-Takt** ensures optimum oil change intervals, a high corrosion protection and low oil and fuel consumption.

Application Note

RAVENOL WATERCRAFT 4-Takt is suitable for use in water-cooled 4-stroke engines operating in both fresh and sea water environments, and especially where a lubricant is required to meet NMMA FC-W standard. Follow the manufacturer's recommendations!

Characteristics

- Exceptional corrosion protection in all oil-wetted engine parts
- An adhesive, pressure-and temperature-resistant oil film
- An excellent anti-wear properties
- A strong detergency and clean burning with no deposits
- Low coking
- High wear protection

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	864,0	EN ISO 12185
Colour		blau	VISUELL
Viscosity at 100 °C	mm²/s	14,3	DIN 51562-1
Viscosity at 40 °C	mm²/s	98,9	DIN 51562-1
Viscosity Index VI		148	DIN ISO 2909
Pourpoint	°C	-30	DIN ISO 3016
tbn	mg KOH/g	8,0	ASTM D2896

All indicated data are approximate values and are subject to the commercial fluctuations.