



1L | 1153210-001

4L | 1153210-004

5L | 1153210-005

10L | 1153210-010

20L | 1153210-020

20L | 1153210-B20

60L | 1153210-060

208L | 1153210-208

1000L | 1153210-700

RAVENOL WATERCRAFT Mineral 2-Takt

Kategorie: 2 stroke engine oil

Artikelnummer: 1153210

Specification: API TC, ISO L-EGB, JASO FB

Oil type: Mineral

Approvals: NMMA TC-W3, RL-29901H

Application: Marine

RAVENOL WATERCRAFT Mineral 2-Takt is 2-stroke engine oil based on high quality base oils with an ash less additive package for optimum lubricity and excellent corrosion protection.

RAVENOL WATERCRAFT Mineral 2-Takt is especially designed for use in fresh water-cooled outboard engines with separate (Auto lube systems) or mixed lubrication.

RAVENOL WATERCRAFT Mineral 2-Takt meets the requirements of the National Marine Manufacturers Association NMMA TC-W3 (CE 50S Yamaha, Mercury).

Application Note

RAVENOL WATERCRAFT Mineral 2-Takt is recommended for "TC-W3" Fluids in all outboard engines according to the prescribed mixing ratio from the engine manufacturer. It can also be used for engines operating in seawater. Typical mixing ratio: 1: 50.

Follow the manufacturers recommendations!

Characteristics

- Contains additives, designed on the characteristics of outboard engine
- An excellent corrosion protection in all oil-wetted engine parts
- Immediate, homogeneous mixture with the used fuel (including lead-free)
- An effective pressure and temperature resistant oil film
- An excellent anti-wear performance
- A clean burning with no deposits
- Low coking
- High wear protection

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		blau	VISUELL
Viscosity at 100 °C	mm²/s	9,7	DIN 51562-1
Viscosity at 40 °C	mm²/s	70,0	DIN 51562-1
Viscosity Index VI		118	DIN ISO 2909
Density at 20 °C	kg/m³	872,0	EN ISO 12185
Flashpoint	°C	>100	DIN EN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.