



1L | 1153310-001

4L | 1153310-004

10L | 1153310-010

20L | 1153310-020

20L | 1153310-B20

60L | 1153310-060

208L | 1153310-208

1000L | 1153310-700

RAVENOL SNOWMOBILES Mineral 2-Takt

Kategorie: 2 stroke engine oil

Artikelnummer: 1153310

Specification: API TC, ISO L-EGB

Oil type: Mineral

Approvals: JASO FB (M049RAV157)

Recommendation: Arctic Cat, Bombardier, Kawasaki, Polaris, Ski-Doo, Suzuki, Yamaha

RAVENOL SNOWMOBILES Mineral 2-Takt is high quality 2-stroke engine oil based on mineral base oils with an ash less additive package for optimum lubricity and excellent corrosion protection.

Application Note

RAVENOL SNOWMOBILES Mineral 2-Takt is recommended for typical mixing ratio: 1: 50 **RAVENOL SNOWMOBILES Mineral 2-Takt** is particularly suitable for remote lubrication and self-mixing systems. The usage in separate lubrication systems with this product will ensure optimum lubrication and minimizes smoke environmentally friendly.

RAVENOL SNOWMOBILES Mineral 2-Takt is ideal for lubricating two-stroke snowmobiles with suitable water cooling.

RAVENOL SNOWMOBILES Mineral 2-Takt is an especially developed high performance engine oil, suitable for use in self-mixing SNOW MOBILE for both air-cooled as well as for water-cooled two-stroke gasoline engines.

Characteristics

- An excellent corrosion protection in all oil-wetted engine parts
- Immediate, homogeneous mixture with the used fuel (including lead-free)
- An effective pressure and temperature resistant oil film
- An excellent anti-wear performance
- A clean burning with no deposits
- Low coking
- High wear protection

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		blau	VISUELL
Viscosity at 100 °C	mm²/s	9,7	DIN 51562-1
Viscosity at 40 °C	mm²/s	70,0	DIN 51562-1
Viscosity Index VI		118	DIN ISO 2909
Density at 20 °C	kg/m³	872,0	EN ISO 12185
Flashpoint	°C	>100	DIN EN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.