



1L | 1163100-001

4L | 1163100-004

10L | 1163100-010

20L | 1163100-020

20L | 1163100-B20

60L | 1163100-060

208L | 1163100-208

1000L | 1163100-700

RAVENOL MARINEOIL DIESEL SHPD SAE 15W-40

Kategorie: Marine engine oil

Artikelnummer: 1163100

Viscosity: 15W-40

Specification: ACEA B4, ACEA E7, API CF, API CI-4

Oil type: Mineral

Recommendation: Caterpillar, Detroit Diesel, IVECO, MAN, Mercruiser, MTU, NANNI Diesel, PERKINS, SKL, STEYR, SULZER, VETUS DEUTZ, VOLVO PENTA, VOLVO VDS-3, Yanmar

Application: Marine

RAVENOL MARINE OIL DIESEL SHPD SAE 15W-40 is an all-year SHPD engine oil for marine diesel engines with or without turbo charging.

RAVENOL MARINE OIL DIESEL SHPD SAE 15W-40 is marine diesel engine motor oil with high wear protection.

RAVENOL MARINE OIL DIESEL SHPD SAE 15W-40 is specially designed for extended oil change intervals (under consideration of the manufacturer instruction).

Characteristics

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	879,5	EN ISO 12185
Colour		Blau	VISUELL
Viscosity at 100 °C	mm²/s	15,0	DIN 51562-1
Viscosity at 40 °C	mm²/s	115,7	DIN 51562-1
Viscosity Index VI		134	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	238	DIN EN ISO 2592
tbn	mg KOH/g	10,5	ASTM D2896

All indicated data are approximate values and are subject to the commercial fluctuations.