



RAVENOL MARINEOIL PETROL SAE 20W-50

Kategorie: Marine engine oil

Artikelnummer: 1163210

Viscosity: 20W-50

Specification: API SL

Oil type: Mineral

Recommendation: Kohler, Mercruiser, VOLVO PENTA AB, Yanmar

Application: Marine

RAVENOL MARINEOIL PETROL 20W-50 is a multi-range engine oil for marine gasoline engines.

RAVENOL MARINEOIL PETROL 20W-50 corresponds to the demands of the SAE class 20W-50. This viscosity classification guarantees a good lubricating film also under complicate operating conditions.

Characteristics

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions
- a good water separation behaviour

1L | 1163210-001

4L | 1163210-004

10L | 1163210-010

20L | 1163210-020

20L | 1163210-B20

60L | 1163210-060

208L | 1163210-208

1000L | 1163210-700

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	878,2	EN ISO 12185
Colour		blau	VISUELL
Viscosity at 100 °C	mm²/s	18,5	DIN 51562-1
Viscosity at 40 °C	mm²/s	161,0	DIN 51562-1
Viscosity Index VI		129	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	247	DIN EN ISO 2592
tbn	mg KOH/g	10,7	ASTM D2896
Sulphated Ash	%wt.	1,42	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.