



5L | 1310100-005
20L | 1310100-020
20L | 1310100-B20
60L | 1310100-060
208L | 1310100-208
1000L | 1310100-700

RAVENOL STOU SAE 10W-30

Kategorie: Engine oil for agricultural vehicles and construct

Artikelnummer: 1310100

Viscosity: 10W-30

Specification: ACEA E3, API CG-4, API GL-4, API SF

Recommendation: ACEA E3, Allison C4, API CG-4/SF, API GL-4, Atlas Copco Kompressor, Caterpillar TO-2, DTFR 15B110 (MB 228.3), Getriebeöl: SAE 80W, Hydrauliköl: HVLP ISO VG 68, Kompressorenöl: Holman Compair Kompressor, MAN 270, Massey Ferguson M1139, Massey Ferguson M1144, Massey Ferguson M1145, MB 227.1, MB 228.1, MB 228.3, MIL-L-2104 D, Motorenöl: SAE 10W-30, New Holland / Ford ESN-M2C-15- 9B, Spezialtraktorenöl: John Deere J27, ZF TE-ML 06A, ZF TE-ML 06B, ZF TE-ML 06D, ZF TE-ML 07B

Application: Agricultural machinery

RAVENOL STOU SAE 10W-30 is a multifunctional lubricating oil for agricultural machinery, excavators and construction machinery and is formulated with top-grade solvent refined base oils and additives.

RAVENOL STOU SAE 10W-30 meets the recommendations of all well known tractor manufacturers and is equal to use in engines, transmissions and hydraulic systems of modern tractors. Ensures trouble-free operation of all units in all seasons. Suitable for wet brakes and shaft coupling (PTO clutches).

Application Note

RAVENOL STOU SAE 10W-30 has a wide range of applications in engines, transmissions and hydraulic systems of modern tractors.

RAVENOL STOU SAE 10W-30 is suitable as an engine oil for gasoline engines and intake and turbo charged diesel engines, also as gear oil (including wet brakes) and as hydraulic oil.

Characteristics

- A powerful dispersion and detergency
- Protection against wear, corrosion and foam
- High resistance to oxidation
- Excellent extreme pressure properties
- A high and stable viscosity index

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	867,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm²/s	11,7	DIN 51562-1
Viscosity at 40 °C	mm²/s	74,7	DIN 51562-1
Viscosity Index VI		151	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	226	DIN EN ISO 2592
tbn	mg KOH/g	12,4	ASTM D2896
Sulphated Ash	%wt.	1,58	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.