



RAVENOL Mehrzweckfett OML

Kategorie: Grease

Artikelnummer: 1340101

Specification: DIN 51502: K2K-30, ISO 6743-9: ISO-L-XCCEA2

Application: Passenger car, Truck, Agricultural machinery, Industry

RAVENOL Mehrzweckfett OML is lithium saponified multipurpose grease with oxidation and corrosion protective additives.

RAVENOL Mehrzweckfett OML has an extreme mechanical stability and a very low friction value. Therefore it can be transported easily.

Application Note

RAVENOL Mehrzweckfett OML is used for the lubrication of easy loaded antifriction bearings and machine components. It is also suited as multipurpose lubrication grease for vehicles.

Characteristics

- Universal use, multipurpose characteristic for a mixed car pool
- Extreme shear stability
- Excellent corrosion protection
- Excellent wear protection
- Very good mechanical and chemical stability
- Very good aging resistant
- Good pumpability, even at low temperatures



0.1L | 1340101-100

0.4L | 1340101-400

5L | 1340101-005

10L | 1340101-010

15L | 1340101-015

180L | 1340101-180

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		hellbraun	VISUELL
Kinematic Viscosity (Base Oil) at 40 °C	mm²/s	130	DIN 51562-1
VKA Pressure Carrying Capacity	N	2000 - 2200	DIN 51350-4
Thickener		Lithium-Komplexseifen	DIN 51757
NLGI-Class		2	DIN 51818
Product Classification		K2K-30	DIN 51502
Working Temperature	°C	-30 / +120	DIN 51825
Short term temperature up to	°C	130	DIN 51757
Worked Penetration at 60 Strokes	mm/10/25°C	265-295	ISO 2137
Corrosion (SKF Emscor dist. Water)	Korr. Grad	1	DIN 51802
Dropping Point	°C	>180	DIN ISO 2176
Copper Corrosion (24h/120 °C)		1	DIN 51811
Water Resistance (3h/90 °C)	°C	1-90	DIN 51807-1

All indicated data are approximate values and are subject to the commercial fluctuations.